



Golani Comercial Ltda
Materiais Elétricos

PARTIDA DIRETA PARA MOTORES TRIFÁSICOS

POTÊNCIA DOS MOTORES TRIFÁSICOS 220 V (CV)	CORRENTE MÁXIMA ADMISSÍVEL (A)			
		CONTATOR	RELÉ	DISJUNTOR MOTOR
0,5	2,5	LC1D09	LRD07 1,6 - 2,5 A	GV2ME07 1,6 - 2,5 A
1,0	3,7	LC1D09	LRD08 2,5 - 4,0 A	GV2ME08 2,5 - 4,0 A
1,5	5,5	LC1D09	LRD10 4,0 - 6,0 A	GV2ME10 4,0 - 6,3 A
2,0	8,0	LC1D09	LRD14 7,0 - 10,0 A	GV2ME14 6,0 - 10,0 A
3,0	9,0	LC1D09	LRD14 7,0 - 10,0 A	GV2ME14 6,0 - 10,0 A
4,0	12,0	LC1D12	LRD16 9,0 - 13,0 A	GV2ME16 9,0 - 14,0 A
5,0	16,0	LC1D18	LRD21 12,0 - 18,0 A	GV2ME20 13,0 - 18,0 A
7,5	23,0	LC1D25	LRD22 16,0 - 24,0 A	GV2ME21 17,0 - 23,0 A
10,0	32,0	LC1D32	LRD32 23,0 - 32,0 A	GV2ME32 24,0 - 32,0 A